

T-3

METAPACE T-3

Economical fully equipped top quality printer

Technical Specifications

PRINT

Printing method	Direct thermal
Print speed	max. 300 mm/Sek.
Print width	max. 72 mm
Resolution	7 Punkte/mm (180 dpi)
Character size	Font A: 42, font B: 56, font C: 56
Sensors	Paper Near End, Paper End, Cover Open, Visibility Intelligence Sensor

MEDIA

Media type	Thermal paper
Paper feed	Easy paper loading
Width	79.5 mm ± 0.5 mm, optional: 58 mm
Roll diameter	max. 83 mm
Media strength	0,062–0,075 mm

ELECTRONICS

Memory	64MB
Interfaces	USB 2.0 (integrated), optional: Parallel, Ethernet, RS-232, WLAN, Bluetooth V5.2
Power supply	AC 120V-230V ± 10%, DC 24V, 2.3A (included)
Barcodes	1D: EAN-13, EAN-8, Code 39, Code 93, Code 128, ITF, Codabar, UPC-A, UPC-E; 2D: PDF417, QR Code, Data Matrix
Emulation	ESC / POS
Reliability	150 km TPH, 1.800.000 cuts, 70.000.000 lines

SOFTWARE

Drivers	Windows Driver, OPOS/JPOS Driver, Linux/Mac CUPS Driver, Virtual COM USB/ Ethernet Driver, Utility Program, Network Auto Installer
Emulation	ESC / POS
SDK	Android (starting with Version 2.2), iOS (starting with Version 5.1.1)

SPECIFICS

Lieferumfang	USB cable (A/B), power adapter + power cable (EU), CD (drivers, utilities), QSG, splash water cover, cable cover, cleaning pen, buzzer, test receipt roll
--------------	---

WARRANTY

Period	60 months
--------	-----------

HOUSING

Dimensions (W x D x H)	148 x 200 x 150 mm
Farbe	Schwarz

CONDITIONS

Temperature	Operating:	0°C to 40°C (32°F to 104°F)
	Storage:	-20°C to 60°C (-4°F to 140°F)
Humidity	Operating:	10% to 80% RH
	Storage:	10% to 90% RH

Highlights

- + Extremely reliable direct thermal printer with a 60-month warranty
- + Lightning-quick printing of slips and receipts with up to 300mm/sec.
- + Easy connection via integrated USB port
- + Versatile options: serial, parallel, Ethernet and Wi-Fi
- + Entirely out-of-the-box: just unpack and start
- + Intelligent sensor



UNPACK AND
GET STARTED