LANDI



LANDI Empowering Connections, Creating a Digital Future

Unleash your terminal's potential with unshakeable support

The C20SE is a perfect combination of stability, lightweight construction, durability, and aesthetics, designed to deliver a seamless customer experience right at the point of interaction.

www.landiglobal.com

- The durable aluminum alloy design with a triangular base offers stability and balance
- Engage consumers with a large multimedia touchscreen and user-friendly interface
- Intuitive cable management for a clean and professional look



| SPECIFICATIONS

Processor	64-bit ARM Cortex Quad-Core, 2.0GHz	Connectivity	Wi-Fi: IEEE802.11 a/b/g/n/ac 2.4G and 5G, Wi-Fi6 (optional) ETH: 1000M Bluetooth 5.0, support BLE
OS	Android 13		
Memory	2GB RAM + 16GB FLASH 4GB RAM + 32GB FLASH (Optional) 4GB RAM + 64GB FLASH (Optional) MicroSD Card (Up to 2TB)	Audio	Speaker: 5W, 100dB@1m, Dual Speaker MIC: Dual Microphone Headset: 3.5mm audio jack
		Camera	Optional 1: NONE Optional 2: 0.3M pixels, QR code scan (Only supported on the 10.1" Premium CFD) Optional 3: Facial recognition ability camera (USB device, plug into Main display edge
Main display	15.6″ at 1920x1080 FHD capacitive multi-touch		
Customer display	Optional 1: None Optional 2 : 10.1" Standard CFD (1280x800 display only) Optional 3 : 10.1" Premium CFD (1280x800, Touch panel, QR Camera, NFC)		expansion port)
		NFC	Optional, Android NFC, ISO / IEC 14443 ISO15693 compliant, support Type A / B, Mifare, Felica (Only supported on the 10.1'' Premium CFD)
Ports	 USB Type-C, download software and application debug USB Type-A 2.0 + 1*USB Type-A 3.0 RJ22 SerialPort RJ45 Ethernet Port RJ11 Cash Drawer Port 3.5mm Audio jack Micro SD slot Power Port 	Power Supply	19V/2.1A
		Environment	Operating temperature: -10°C to +50°C Storage temperature: -20°C to +70°C Operating humidity: 10% to 90% non-condensing
keypad	1 Power key with indicator light (Red&blue) 2 Volume keys	Certification	CE/CB/FCC/IC/WEEE/RoHS

гулы



